

## SPLIT-CORE TRANSFORMERS (ENCAPSULATED IN RESIN)



SPLIT-CORE TRANSFORMERS																		
MODEL	TA30R			TA60R			TA80R			TA100R			TA125R			TA160R		
Bus-Bar	30x20			60x30			80x50			100x80			125x80			160x80		
Cable	Ø20			Ø30			Ø50			Ø80			Ø80			Ø80		
Accuracy	0,5	1	3	0,5	1	3	0,5	1	3	0,5	1	3	0,5	1	3	0,5	1	3
I <sub>pn</sub> (A)	VA			VA			VA			VA			VA			VA		
100	3																	
150	3,75																	
200	2,5 4																	
250	3,75 5			2,5 3,75			2,5 3,75			2,5 3,75								
300	2,5 4 6			3,75 5			3,75 5			3,75 5								
400	3,75 5 10			2,5 3,75 7,5			2,5 3,75 7,5			2,5 3,75 7,5								
500				3,75 5 15			3,75 5 15			3,75 5 15			5 7,5			2,5 3,75 7,5		
600				5 7,5 20			5 7,5 20			5 7,5 20			5 15			3,75 5 10		
750				7,5 10 20			7,5 10 20			7,5 10 20			5 10 20			5 10 20		
800				7,5 10 20			7,5 10 20			7,5 10 20			7,5 10 20			7,5 10 20		
1000				10 15 20			10 15 20			10 15 20			10 20 30			10 20 30		
1200										15 20 30			15 20 30			15 20 30		
1500										15 20 30			20 30 45			20 30 45		
2000										20 30 45			25 30 45			25 30 45		
2500													25 30 45			25 30 45		
3000													30 45 60			30 45 60		
4000																30 45 60		
5000																30 45 60		

### DIMENSIONS

**TA-R**

MODELS	A	B	C	D	E	F
TA30R	32	21	105	90	99	114
TA60R	62	32	130	100	109	139
TA80R	82	52	150	120	129	159
TA100R	104	82	172	150	159	181
TA125R	127	82	195	150	159	204
TA160R	162	82	230	150	159	239

Dimensions in mm.